## Stainless Steel Globe Valve

## Feature


200# WSP/WOG Stainless steel body & trim FNPT x FNPT Threaded ends (ASME B1.20.1-NPT) Inserted bonnet Rising stem Swivel type disc Inspect and test comply to API 598

Pressure / Temperature rating					
200# WSP/WOG	350 °F max. temp.				



## Material

	Part	Material	Specification		
1	Body	Stainless Steel	ASTM A35 CF8M		
2	Disc	Stainless Steel	ASTM A35 CF8M		
3	Gasket	PTFE	-		
4	Bonnet	Stainless Steel	ASTM A35 CF8M		
5	Washer	Stainless Steel	ASTM A276 304		
6	Packing	PTFE	-		
7	Gland	Stainless Steel	AISI 304		
8	Cap nut	Stainless Steel	ASTM A276 304		
9	Stem	Stainless Steel	ASTM A276 316		
10	Handwheel	Aluminum	-		
11	Washer	Stainless Steel	ASTM A276 304		
12	Handwheel nut	Stainless Steel	A2-70		



## Dimension, Cv, Weight

Size	NPT	ΦD	ФW	Н	L	Cv	Weight
	[in]	[in]	[in]	[in]	[in]		[lb]
1/2"	½ - 14 NPT	0.59	2.76	3.70	2.68	3.8	0.90
3/4"	¾ - 14 NPT	0.78	2.76	4.06	3.35	7	1.29
1"	1 - 11.5 NPT	0.98	3.15	4.68	3.54	11	1.86
11/4"	1¼ - 11.5 NPT	1.26	3.15	5.63	4.13	21	2.78
11/2"	1½ - 11.5 NPT	1.57	3.54	5.90	4.72	29	4.51
2"	2 - 11.5 NPT	1.97	3.94	6.69	5.51	50	5.46

